

KK61-6 Flange Galvanized Steel 1" IPS (1.38" ID)



This flange, with holes provided for countersunk flat head screw fixings only, is used on structures where the fixing required is positional only. Frequently used as a wall fixing bracket. Ø indicates diameter of fixing holes. It is not recommended for use as a base flange to support guardrailing or balustrading.

Part	Weight	A	E	F	G	H	diameter of fixing holes
61-3	0.42 lbs.	3	2.76 in.	1.26 in.	1.85 in.	0.24 in.	0.26 in.
61-4	0.51 lbs.	4	2.99 in.	1.54 in.	2.13 in.	0.24 in.	0.26 in.
61-5	0.73 lbs.	5	3.15 in.	1.57 in.	2.24 in.	0.24 in.	0.26 in.
61-6	1.1 lbs.	6	3.54 in.	1.89 in.	2.52 in.	0.24 in.	0.26 in.
61-7	1.36 lbs.	7	4.02 in.	2.01 in.	2.99 in.	0.28 in.	0.26 in.
61-8	1.47 lbs.	8	4.49 in.	2.32 in.	3.5 in.	0.31 in.	0.26 in.
61-9	2.38 lbs.	9	5 in.	2.48 in.	3.74 in.	0.39 in.	0.39 in.