

KK64-8 SPEC SHEET

BuyRailings 71 Commerce Drive Brookfield, CT 06804 T 877-810-4116 F +1-203-930-3620 www.buyrailings.com

KK64-8 Standard Vertical Railing Base Galvanized Steel 1-1/2" IPS (1.94" ID)



This fitting is designed for fixing guardrailing and balustrading to walls, parapets, steps and ramps. The upright cannot drop through the socket. Access to the top fixing hole is restricted by the position of the flange to the barrel. When selecting a hexagon head bolt or similar bolt fixing, the maximum length of the bolt including the head must not exceed 1". Should an upright be required to pass through the fitting, the base can be bored out to order. Ø indicates diameter of fixing holes.

Part 1	Weigh	t A	D	E	F	G	Н	J	K	diameter of fixing holes
64-	1.69	6	3.39	3.74	0.87	2.64 in.	2.24	1.77	1.54	0.55 in.
6	lbs.		in.	in.	in.	in.	in.	in.	in.	
64-	2.46	7	3.31	4.25	1.18	2.83 in.	2.52	1.97	1.18	0.55 in.
7	lbs.	1	in.	in.	in.	in.	in.	in.	in.	
64- 8	3.39 lbs.	8	3.5 in.	4.76 in.	1.26 in.	3.5 in.	2.76 in.	2.28 in.	1.1 in.	0.55 in.