

KK61-4 SPEC SHEET

BuyRailings 71 Commerce Drive Brookfield, CT 06804 T 877-810-4116 F +1-203-930-3620 www.buyrailings.com

KK61-4 Flange Galvanized Steel 1/2" IPS (0.87" ID)



This flange, with holes provided for countersunk flat head screw fixings only, is used on structures where the fixing required is positional only. Frequently used as a wall fixing bracket. Ø indicates diameter of fixing holes. It is not recommended for use as a base flange to support guardrail or balustrading.

Part	Weight	A	E	F	G	H	diameter of fixing holes
61-3	0.42 lbs.	3	2.76 in.	1.26 in.	1.85 in.	0.24 in.	0.26 in.
61-4	0.51 lbs.	4	2.99 in.	1.54 in.	2.13 in.	0.24 in.	0.26 in.
61-5	0.73 lbs.	5	3.15 in.	1.57 in.	2.24 in.	0.24 in.	0.26 in.
61-6	1.1 lbs.	6	3.54 in.	1.89 in.	2.52 in.	0.24 in.	0.26 in.
61-7	1.36 lbs.	7	4.02 in.	2.01 in.	2.99 in.	0.28 in.	0.26 in.
61-8	1.47 lbs.	8	4.49 in.	2.32 in.	3.5 in.	0.31 in.	0.26 in.
61-9	2.38 lbs.	9	5 in.	2.48 in.	3.74 in.	0.39 in.	0.39 in.