

KK62-9 SPEC SHEET

BuyRailings 71 Commerce Drive Brookfield, CT 06804 T 877-810-4116 F +1-203-930-3620 www.buyrailings.com

KK62-9 Standard Railing Flange Galvanized Steel 2" IPS (2.41" ID)



Ideal when a structural fixing is required. When fixing guardrailing and balustrades, Type 62 should always be used. The holes are of sufficient diameter to insure proper fixing with either a mechanical or chemical anchor. The two set screws in the vertical socket give greater side-load stability to the upright. It is recommended that the fixing holes in the flange should be in line with the applied load. Ø indicates diameter of fixing holes.

Part	Weight	A	D	E	F	G	H	diameter of fixing holes
62-5	1.3 lbs.	5	2.52 in.	4.57 in.	2.99 in.	2.99 in.	0.31 in.	0.43 in.
62-6	1.61 lbs.	6	2.99 in.	5.04 in.	3.5 in.	3.5 in.	0.31 in.	0.55 in.
62-7	2.64 lbs.	7	2.95 in.	5.51 in.	3.5 in.	4.02 in.	0.39 in.	0.55 in.
61-8	2.86 lbs.	8	2.95 in.	5.51 in.	3.5 in.	4.53 in.	0.39 in.	0.55 in.
62-9	3.87 lbs.	9	4.02 in.	6.5 in.	5 in.	5 in.	0.39 in.	0.71 in.