


**00130 Reducing Fitting. Offset Cross Aluminum Magnesium 3/4" X 1".**



#10-56 Offset Cross

DIMENSIONS IN INCHES						DIMENSIONS IN MILLIMETERS					
SIZE	A	B	C	D	E	SIZE	A	B	C	D	E
1/2"	1.75	1.75	1.75	1.75	1.75	44.27	44.27	44.27	44.27	44.27	44.27
3/4"	2.00	2.00	2.00	2.00	2.00	50.80	50.80	50.80	50.80	50.80	50.80
1"	2.25	2.25	2.25	2.25	2.25	57.15	57.15	57.15	57.15	57.15	57.15
1 1/4"	2.75	2.75	2.75	2.75	2.75	70.18	70.18	70.18	70.18	70.18	70.18
1 1/2"	3.00	3.00	3.00	3.00	3.00	76.20	76.20	76.20	76.20	76.20	76.20
2"	3.50	3.50	3.50	3.50	3.50	88.90	88.90	88.90	88.90	88.90	88.90
2 1/2"	4.00	4.00	4.00	4.00	4.00	101.60	101.60	101.60	101.60	101.60	101.60
3"	4.50	4.50	4.50	4.50	4.50	114.30	114.30	114.30	114.30	114.30	114.30
3 1/2"	5.00	5.00	5.00	5.00	5.00	127.00	127.00	127.00	127.00	127.00	127.00
4"	5.50	5.50	5.50	5.50	5.50	140.00	140.00	140.00	140.00	140.00	140.00
4 1/2"	6.00	6.00	6.00	6.00	6.00	152.40	152.40	152.40	152.40	152.40	152.40
5"	6.50	6.50	6.50	6.50	6.50	165.10	165.10	165.10	165.10	165.10	165.10
5 1/2"	7.00	7.00	7.00	7.00	7.00	177.80	177.80	177.80	177.80	177.80	177.80
6"	7.50	7.50	7.50	7.50	7.50	190.50	190.50	190.50	190.50	190.50	190.50
6 1/2"	8.00	8.00	8.00	8.00	8.00	203.20	203.20	203.20	203.20	203.20	203.20
7"	8.50	8.50	8.50	8.50	8.50	215.90	215.90	215.90	215.90	215.90	215.90
7 1/2"	9.00	9.00	9.00	9.00	9.00	228.60	228.60	228.60	228.60	228.60	228.60
8"	9.50	9.50	9.50	9.50	9.50	241.30	241.30	241.30	241.30	241.30	241.30
8 1/2"	10.00	10.00	10.00	10.00	10.00	254.00	254.00	254.00	254.00	254.00	254.00
9"	10.50	10.50	10.50	10.50	10.50	266.70	266.70	266.70	266.70	266.70	266.70
9 1/2"	11.00	11.00	11.00	11.00	11.00	279.40	279.40	279.40	279.40	279.40	279.40
10"	11.50	11.50	11.50	11.50	11.50	292.10	292.10	292.10	292.10	292.10	292.10

- Quick and easy way to assemble structural pipe systems • Galvanized malleable iron
- Reduce labor costs by 70% • 100% reusable • No welding or threading • No drilling or bolting

Strong, malleable iron, slip-on pipe fittings with from one to five case-hardened set screws per fitting – depending on the number of pipes to be joined at one joint.

For slip-on aluminum fittings. These fittings can support an axial load of 2000 lbs per set screw with the set screw tightened to a torque of 29 lbs/ft. This is normally obtained when the screw is fully tightened using a ratchet wrench.