



CR3278 Surface Mount Turnbuckle Satin 316 Stainless Steel for 1/8" Cable. Machine Swage Required.



Surface Mount Turnbuckle



Attaches to the face of the end post using lag screws or bolts (sold separately). 130° pivoting allows for angled stair terminations. 130° pivoting allows for angled stair terminations. Typically paired with Fixed Surface Mount or another Surface Mount Turnbuckle.

| Part | Swage | Cable [†] | Thread | OD | Ht | L (close open) |
|------|-------|--------------------|--------|--------|------|------------------|
| 3278 | 1/8" | 1/4-28 | 1/4" | 1-3/8" | 5/8" | 7" (18") |
| 3277 | 3/16" | 1/4-28 | 1/4" | 1-3/8" | 5/8" | 7-1/2" (19-1/2") |
| 3276 | 1/8" | 5/16-24 | 5/16" | 1-1/2" | 3/4" | 8-1/4" (21") |
| 3275 | 1/8" | 1/4-28 | 1/4" | 1-3/8" | 5/8" | 7-3/4" (19-3/4") |
| 3276 | 3/16" | 1/4-28 | 1/4" | 1-3/8" | 5/8" | 8" (21") |

Machine Swage CableCrimp™ Hand Swage

[†] since flanges are formed pieces, allow a tolerance of a 1/16" on flange hole span dimension (H)

Attaches to the face of the end post using lag screws or bolts (sold separately). 130° pivoting allows for angled stair terminations. Typically paired with Fixed Surface Mount or another Surface Mount Turnbuckle.

[Hand Cable Crimp Instructions](#) 