


BuyRailings 71 Commerce Drive Brookfield, CT 06804 T 877-810-4116 F +1-203-930-3620 www.buyrailings.com

49-851R/F Radius Glass Grip - Satin Stainless Steel 316 for Medium Grips Glass Thickness 1/4" or 3/8". Mounts to Flat Surface



Radius Glass Grips

ITEM #	MATERIAL	FINISH	W	H	D	GLASS THICKNESS	MOUNTS ON TO
SMALL GRIPS							
49-850R/424	316	Satin	1.5"	1.95"	1"	1/2" or 3/4"	1.62" Tube
MEDIUM GRIPS							
49-851R/F	316	Satin	1.7"	1.7"	.94"	1/4" or 3/8"	Flat Surface
49-851R/1H	316	Satin	1.7"	1.7"	.94"	1/4" or 3/8"	1.5" Tube
49-851R/424	316	Satin	1.7"	1.7"	.94"	1/4" or 3/8"	1.62" Tube
LARGE GRIPS							
49-860R/F	316	Satin	2.32"	2.30"	1.3"	1/4" or 3/8"	Flat Surface
49-860R/2	316	Satin	2.32"	2.30"	1.3"	1/4" or 3/8"	2" Tube
EXTRA LARGE GRIPS							
49-850R/424	316	Satin				1/2"	1.62" Tube



Rubber Inserts for Radius Glass Grips

ITEM #	USE WITH	GLASS THICKNESS
85-G21007	Small Grips	1/4"
85-G21008	Small Grips	3/8"
85-G21009	Medium Grips	1/4"
85-G21010	Medium Grips	3/8"
85-G21011	Large Grips	3/8"
85-G21011	Large Grips	1/2"
85-G21015	Extra Large Grips	1/2"



- Rubber Inserts for Radius Glass Grips (Set of 2) Are Sold separately. Item# GGI10.
- Glass clamps have a pin. The pin diameter is 6mm.

INSTALLATION Remove the side plate that is mounted with two screws and remove pin. Mount glass grip to tube using a M8 x 1.25 pitch screw, 20mm long. Replace pin, mount glass and then replace the side plate.