

BuyRailings 71 Commerce Drive Brookfield, CT 06804 T 877-810-4116 F +1-203-930-3620 www.buyrailings.com

49-851R/F Radius Glass Grip - Satin Stainless Steel 316 for Medium Grips Glass Thickness 1/4" or 3/8". Mounts to Flat Surface



Radius Glass Grips

ITEM #	MATERIAL	FINISH	N	H	Ø	Ø HOLE (MIN/MAX)	Ø Ø HOLE (MIN/TO)
SMALL SIZE							
49-851R/F	316	Satin	1.0"	1.0"	1"	1/4" or 3/8"	1.07" Dia
MEDIUM SIZE							
49-851R/F	316	Satin	1.7"	1.7"	3/4"	1/4" or 3/8"	2.55" Dia
49-851R/F	316	Satin	1.7"	1.7"	3/4"	1/4" or 3/8"	1.75" Dia
49-851R/F	316	Satin	1.7"	1.7"	3/4"	1/4" or 3/8"	1.52" Dia
LARGE SIZE							
49-851R/F	316	Satin	2.32"	2.32"	1.5"	1/4" or 3/8"	2.55" Dia
49-851R/F	316	Satin	2.32"	2.32"	1.5"	1/4" or 3/8"	2" Dia
EXTRA LARGE SIZE							
49-851R/F	316	Satin			3"	1/4" or 3/8"	



Rubber Inserts for Radius Glass Grips

ITEM #	Ø HOLE (MIN/TO)	Ø HOLE (MIN/TO)
85-22107	Small Grip	1.4"
85-22108	Small Grip	2.0"
85-22109	Medium Grip	1.4"
85-22110	Medium Grip	1.8"
85-22111	Large Grip	2.0"
85-22112	Extra Large Grip	1.8"

- Rubber Inserts for Radius Glass Grips (Set of 2) Are Sold separately. Item# GGI10.
- Glass clamps have a pin. The pin diameter is 6mm.

INSTALLATION Remove the side plate that is mounted with two screws and remove pin. Mount glass grip to tube using a M8 x 1.25 pitch screw, 20mm long. Replace pin, mount glass and then replace the side plate.