

49-860R/F Radius Glass Grip - Satin Stainless Steel 316 for Small Grips Glass Thickness 3/8" or 1/2". Mounts to Flat Surface



Radius Glass Grips

ITEM #	MATERIAL	FINISH	N	H	R	GLASS THICKNESS	WIDTH (IN/FT)
STANDARD							
49-860R/F	316	Satin	1.7"	1.7"	0"	3/8" or 1/2"	1.67" Dia
ALTERNATE							
49-860R	316	Satin	1.7"	1.7"	0"	3/8" or 1/2"	1.67" Dia
49-860R/F	316	Satin	1.7"	1.7"	0"	3/8" or 1/2"	1.67" Dia
49-860R/F	316	Satin	1.7"	1.7"	0"	3/8" or 1/2"	1.67" Dia
LONG GRIPS							
49-860R/F	316	Satin	2.38"	2.38"	0"	3/8" or 1/2"	1.67" Dia
49-860R	316	Satin	2.38"	2.38"	0"	3/8" or 1/2"	1.67" Dia
OTHER APPLICATIONS							
49-860R/F	316	Satin			0"	1/2" Tube	



Rubber Inserts for Radius Glass Grips

ITEM #	USE WITH	GLASS THICKNESS
49-221007	Small Grips	1/4"
49-221008	Small Grips	3/8"
49-221009	Medium Grips	1/2"
49-221010	Medium Grips	3/4"
49-221011	Large Grips	3/4"
49-221012	Large Grips	1/2"



- Rubber Inserts for Radius Glass Grips (Set of 2) Are Sold separately. Item# GGI10.
- Glass clamps have a pin. The pin diameter is 6mm.

INSTALLATION Remove the side plate that is mounted with two screws and remove pin. Mount glass grip to tube using a M8 x 1.25 pitch screw, 20mm long. Replace pin, mount glass and then replace the side plate.