

BuyRailings 71 Commerce Drive Brookfield, CT 06804 T 877-810-4116 F +1-203-930-3620 www.buyrailings.com

49-860R/F Radius Glass Grip - Satin Stainless Steel 316 for Small Grips Glass Thickness 3/8" or 1/2". Mounts to Flat Surface



Radius Glass Grips

ITEM #	MATERIAL	FINISH	N	H	R	GLASS THICKNESS	GLASS WIDTH
SMALL GRIPS							
49-860R/F	316	Satin	1.0"	1.0"	1"	1/2" or 3/8"	1.67" Dia
MEDIUM GRIPS							
49-861R/F	316	Satin	1.7"	1.7"	3/4"	1/2" or 3/8"	2.5" Dia
49-861R/H	316	Satin	1.7"	1.7"	3/4"	1/2" or 3/8"	1.5" Dia
49-862R/F	316	Satin	1.7"	1.7"	3/4"	1/2" or 3/8"	1.5" Dia
LARGE GRIPS							
49-863R/F	316	Satin	2.32"	2.32"	1.5"	1/2" or 3/8"	2.5" Dia
49-863R/H	316	Satin	2.32"	2.32"	1.5"	1/2" or 3/8"	2" Dia
EXTREMELY LARGE GRIPS							
49-864R/F	316	Satin			3"	1/2" Dia	



Rubber Inserts for Radius Glass Grips

ITEM #	SIZE (W x H)	GLASS THICKNESS
85-2210T	Small Grip	1/4"
85-2210S	Small Grip	3/8"
85-2210M	Medium Grip	1/4"
85-2210L	Medium Grip	3/8"
85-2210H	Large Grip	3/8"
85-2210L	Large Grip	1/2"

- Rubber Inserts for Radius Glass Grips (Set of 2) Are Sold separately. Item# GGI10.
- Glass clamps have a pin. The pin diameter is 6mm.

INSTALLATION Remove the side plate that is mounted with two screws and remove pin. Mount glass grip to tube using a M8 x 1.25 pitch screw, 20mm long. Replace pin, mount glass and then replace the side plate.