

CAPUL-6-2.375 Pull-Lock Stop-End Fitting Stainless Steel 316. 2-3/8" Tube and 3/16" Cable.



No field swaging

Pull-Lock® fittings are designed for use with 1x19 L.H. lay strand only. They can be used with any tensioning device on the other end, and when matched with an Invisiware® Receiver tensioner (page 11), gives you a cable railing system with no visible hardware between the end posts.

Easy to install

You can order your cables with a tensioner already on one end or you can install a tensioner on one end on site. Attach the tensioner on one end post, slip the Pull-Lock® fitting into the other end post and pull the cable all the way through the Pull-Lock® fitting. Tension the cables, then cut the excess cable off on the back side of the fitting with a 4-inch right angle grinder or a cutting wheel (available from the factory) that is used with your hand drill. Press on the stainless steel cap to cover the bare cable end, and you're done!

Use with metal or wood posts

Pull-Lock® fittings come in four lengths, so that when used with a matching length Invisiware Receiver, post-drilling is made uniform. Pull-Lock® fittings work with pipe and with round, square, or rectangular metal tubing. When used with an end post 1½" or more in thickness, the Pull-Lock® fitting is hidden inside the end post, with only the head exposed on the outside of the post. Pipe ends are counterbored, so the full perimeter of the screw cap head rests on a flat surface in the pipe. The head rests on the outside wall of a flat-sided metal post. A plastic washer is included and acts as a scratch-resistant barrier between the screw cap head and the metal post. For wood applications, also order 7/16SAE stainless steel washer.

No field swaging

- They can be used with the Invisiware® Receiver on the other end or any tensioning device.
- Compatible 1x19 L.H. LAY STRAND ONLY.
- End Cap Included
- Tools needed: 29/64" drill bit