

49-C424/36/W/B/S/AS


SPEC-SHEET

49-C424/36/W/B/S/AS 36" Round Stair Center Post (1.67"/42.4mm OD/0.08" Wall) - Fascia Mount - Adjustable Saddle - Satin 316 Stainless Steel - for 1/8" or 3/16" Cable





CableRail Previous Projects Gallery



Prefabricated Floor Mount Posts for 1/8" Cable: 36" Standard height. Post includes the pre-drilled holes, welded flange, flange canopy cover and top saddle (stair post saddle is adjustable). When ordering any **STAIR** Prefabricated Post for Cable Railings. Please provide the rise and run information for us to calculate the center-to-center hole spacing of the posts. **If your stairs are not angled at 34° then please download the Cable & Stair Angle Specifications order** form here and email it or fax back to us.

Center = Center Post. 0.08" Wall

End = End Post. Post drilled for the 224 and 232 Cable Rail Series. Post has thicker 0.14" \Wall

End Stair = Beginning or End Post. Angle drilled holes for stair installation at 34°. 0.14" Wall". Use 2-3/8" Cable Fittings (224 Series) Stair = Angle drilled holes for stair installation. 0.08" Wall

Corner = Corner Post is fabricated with two 90 degree drilled holes permitting the use of a single post corner instead of a double post corner. Post has thicker 0.14" Wall (Contact a representative for more details)

**Important:

- Cable Rail installation with directional changes must not exceed 40 feet or 2 Corners.
- Straight installation of Cable Rail can extend up to a maximum of 50 feet.
- For double corner posts, do not space more than 4" apart.
- Spacing between posts must not exceed 4 Feet.
- Wall fascia mounting bolts are NOT included.

Cable Installation With Metal Posts

BuyRailings • 71 Commerce Drive, Brookfield, CT 06804 • T 877-810-4116 • F +1-203-930-3620 • buyrailings.com