

49-860R/2 Radius Glass Grip - Satin Stainless Steel 316 for Large Grips Glass Thickness 3/8" or 1/2". Mounts to 2" Tube



Radius Glass Grips

ITEM #	MATERIAL	FINISH	N	H	W	GLASS THICKNESS	INSTALL TO
SMALL GRIPS							
49-860R/2	316	Satin	1.5"	1.5"	1"	3/8" or 1/2"	1.875" Tube
MEDIUM GRIPS							
49-860R/2	316	Satin	1.7"	1.7"	1.25"	3/8" or 1/2"	2.0" Tube
49-860R/2	316	Satin	1.7"	1.7"	1.25"	3/8" or 1/2"	2.0" Tube
49-860R/2	316	Satin	1.7"	1.7"	1.25"	3/8" or 1/2"	2.0" Tube
LARGE GRIPS							
49-860R/2	316	Satin	2.50"	2.50"	1.5"	3/8" or 1/2"	2.5" Tube
49-860R/2	316	Satin	2.50"	2.50"	1.5"	3/8" or 1/2"	2.5" Tube
EXTRA LARGE GRIPS							
49-860R/2	316	Satin			1.5"	3/8" or 1/2"	2.5" Tube



Rubber Inserts for Radius Glass Grips

ITEM #	USE WITH	GLASS THICKNESS
49-860R/2	Small Grips	1/2"
49-860R/2	Small Grips	3/8"
49-860R/2	Medium Grips	1/2"
49-860R/2	Medium Grips	3/8"
49-860R/2	Large Grips	3/8"
49-860R/2	Large Grips	1/2"
49-860R/2	Extra Large Grips	1/2"

- Rubber Inserts for Radius Glass Grips (Set of 2) Are Sold separately. Item# GGI10.
- Glass clamps have a pin. The pin diameter is 6mm.

INSTALLATION Remove the side plate that is mounted with two screws and remove pin. Mount glass grip to tube using a M8 x 1.25 pitch screw, 20mm long. Replace pin, mount glass and then replace the side plate.